

NOTES:

- TREES AND HARDSCAPE IN PLANTER STRIP SUBJECT TO APPROVAL OF THE CITY ENGINEER.
 CONSTRUCTION IN PLANTER STRIP SUBJECT TO ENCROACHMENT PERMIT FROM ENGINEERING
 DIVISION.
- 2. FOR CURB AND SIDEWALK SCORING SEE SD-8. CONCRETE SHALL BE 6-SACK.
- 3. WHEN FACE OF CURB TO PROPERTY LINE EQUALS 10', SIDEWALK SHALL BE 4'-6" AND PLANTER STRIP SHALL BE 5'-0".
- 4. IF DRIVEWAY AND CURBS ARE NOT PLACED IN MONOLITHIC POUR USE NO. 3 REBAR DOWELS 12" LONG @ 2'-0" ON CENTER. EPOXY IF DRILLED.
- 5. LIMITS OF THE REMOVAL OF EXISTING CURB, GUTTER, SIDEWALK AND ASPHALT SHALL BE DETERMINED IN THE FIELD BY THE CITY INSPECTOR.

SD-10B-06.DWG A		AS SHO	WN	DC	KC	04/11/06	SD-10B	1 of 1
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
REVISIONS							CITY ENGINEER	
NO.	REVISED	DATE	RESID	RESIDENTIAL - RETROFIT (Nam Hughes	
			TYPE "A" DRIVEWAY APPROACH				, 11	
			STANDARD DETAILS			RESOLUTION NO. 2006-31		
			CII	Y OF			04/11/06	
						\	DATE APPROVED BY CITY COUNCIL	