

NOTES:

- 1. ON MEDIANS LESS THAN 14 FEET WIDE, REPLACE MAINTENANCE BAND WITH 18 INCH MINIMUM WIDTH PLANTING OF WALKABLE GROUNDCOVER.
- 2. IF CONCRETE, INSTALL DEEP JOINTS TO MATCH CURB & GUTTER DEEP JOINTS. SEE ENGINEERING STANDARD DETAIL 8 FOR DEFINITION OF DEEP JOINT.
- 3. FOR PAVERS WITHIN THE DRIPLINE OF AN EXISTING TREE, HAND EXCAVATE ALL AREAS.
 6" THICK, CLASS 2 PERMEABLE LAYER MAY BE REDUCED OR ELIMINATED, IF NECESSARY.
 SEE LSD-9 FOR TREE PRESERVATION NOTES.
- 4. PAVERS TO BE: 6 X 9 X 3 1/8 CALSTONE PERMEABLE PAVING UNITS, COLOR: RUSTIC YELLOW STONE. SUBSTITUTIONS TO BE APPROVED BY THE CITY LANDSCAPE ARCHITECT.

Pak	General Revision	07/31/22	CIT	Y OF	FREMO	NT	DATE APPROVED BY CITY COUNCIL 12/13/1	
Jak	General Revision	08/2019	STANDARD DETAILS					
Pak	General Revision	n 09/05/12	STANDARD DETAILS				2006-31	
	Council Revision	12/13/11		CITY ST	TANDARD)	-1 05	,
APPR	REVISED	DATE				Nam Bryles		
REVISIONS			MAINTENANCE BAND				CITY ENGINEER	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
LSD-8.DWG		1" = 1'-0"		PM/MM	RER	DEC. 2011	LSD-8	1 of 1