

NOTE:

- 1. INSTALL TOP OF POP-UP SPRINKLER 1 INCH ABOVE FINISHED GRADE IN SHRUB AREAS AND FLUSH WITH FINISHED GRADE IN TURF AREAS. IN TURF FINISH GRADE IS THE TOP OF THE SOD ROOT ZONE WHEN INSTALLED. CONTRACTOR TO ACCOMMODATE FOR VARYING SOD THICKNESS, BASED ON SOD SUBMITTAL.
- 2. ROTOR SHALL BE INSTALLED FLUSH IN TURN AREAS. SEE NOTE #1.
- 3. REFER TO CITY STANDARD DETAIL LSD-14 FOR MATERIALS
- 4. INSTALL A MINIMUM OF 9" FROM EDGE OF PAVEMENT IN SHRUB AREAS AND 2" IN TURF AREAS.

			CITY OF FREMONT STANDARD DETAILS			DATE APPROVED BY CITY COUNCIL 12/13/11 RESOLUTION NO. 2006-31		
Jak	General Revision	07/31/22		017(1407(1)	DEIMIE	5	2000-31	
Jak	General Revision	08/2019	CITY STANDARD				1 05	,
APPR	REVISED	DATE	IRRIGATION ROTOR OR POP-UP				Nam Hughen	
	REVISIONS		INNIGATION NOTON ON FOF-OF				CITY ENGINEER	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
LSD-21.DWG		NONE		AK/MM/PM	RER	NOV. 2005	LSD-21	1 of 1