

NOTES:

- 1. THIS CURB DETAIL IS ONLY REQUIRED WHEN SYNTHETIC SAFETY SURFACING IS NOT FLUSHED WITH ADJACENT PAVING.
- 2. REFER TO DETAIL PSD CONC-3 WHEN ADJACENT SURFACING IS CONCRETE.
- 3. USE 6 SACK 2500 PSI MIX CONCRETE, DARKENED WITH LAMP BLACK, 1 POUND PER CUBIC YARD.
- 4. REFER TO DETAIL PSD PLT-4 WHEN ADJACENT SURFACING IS TO BE PLANTED. DISPLACEMENT SHALL BE:

1 1/2" AT TURF AREAS

2" AT SHRUB & PLANTING AREAS

5. ALL JOINTS SHALL BE CAULKED WITH A POLYURETHANE, ALL PURPOSE FLEXIBLE SEALANT CAPABLE OF ADHERING TO A VERTICAL SURFACE.

0	2"	4"	8"	16"					
	_		***************************************						
S	2" 4" 8" 16" CALE: 1 1/2" = 1'-0"								

			CIT	'Y OF I	FREM(ONT	December 13, 2011	
			PA	RK STAND	ARD DETA	AILS	RESOLUTION NO. 2011-65	
			<u> </u>	PLAY ARE	SENIOR LANDSCAPE ARCHITECT			
APR.	REVISED	DATE	SYNT	HETIC SAFETY SURFACE		COMMUNITY SERVICES DIRECTOR		
REVISIONS							annell Hall	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
PSD CONC-1.DWG		1 1/2" = 1'-0"		MAM	RER	05/06/2011	PSD CONC-1	1 OF 1