



**MANUFACTURER/MODEL:**

1. MURDOCK, M-23 OR M-23-2-PF (W/ PET BOWL), OR APPROVED EQUAL
2. MOST DEPENDABLE FOUNTAINS, 440 OR 440DB( W/ PET BOWL), OR APPROVED EQUAL

**COLOR:** FAIRWAY GREEN EG14; GREEN; OR APPROVED EQUAL

**NOTES:**

1. DRINKING FOUNTAIN TO PROVIDE FLOW OF WATER AT LEAST 4" HIGH TO ALLOW INSERTION OF CUP OR GLASS UNDER FLOW OF WATER.
2. INSTALL WATER AND WASTE CONNECTIONS PER MANUFACTURER'S SPECIFICATIONS.
3. INSTALL ADDITIONAL GATE VALVE AT THE POINT OF CONNECTION, IF GREATER THAN 10 FEET WAY, TO CONTROL ON/OFF OF FLOW CLOSER TO THE SOURCE.
4. CLEAN OUT AND P-TRAP SHALL BE INSTALLED TO THE INVERT DEPTHS AS DESCRIBED ON THE PLANS.
5. SURROUNDING CONCRETE SHALL BE SLOPED TO DRAIN, NOT TO EXCEED 2% IN ANY DIRECTION.



SCALE: 1" = 1'-0"

# CITY OF FREMONT

## PARK STANDARD DETAILS

### DRINKING FOUNTAIN

DATE APPROVED BY CITY COUNCIL  
December 13, 2011

RESOLUTION NO. 2011-65

SENIOR LANDSCAPE ARCHITECT

COMMUNITY SERVICES DIRECTOR

APR.	REVISED	DATE	
<b>REVISIONS</b>			

FILE NO. PSD SF-1.DWG	SCALE 1" = 1'-0"	DRAWN AM	CHECKED RER	DATE 03/09/2011	DWG NO. PSD SF-1	1 OF 1
--------------------------	---------------------	-------------	----------------	--------------------	---------------------	--------